Information sheet (Lot.10)

This information includes the results of calculation of the seasonal energy consumption and efficiency for air conditioner in regards to ErP pursuant to the Commission Regulation(EU) No.206/2012 and No.626/2011.

Information to identify the model(s) to which the information relates to:

TYPE

AIR CONDITIONER
SINGLE SPLIT
WALL MOUNTED
Indoor unit(s)
Outdoor unit
BRAND

AIR CONDITIONER
SINGLE SPLIT
WALL MOUNTED

ASYG24KLCA
COUTTON
FUJITSU

N/A = Not Applicable

Function					
Cooling	Yes	Average	Yes		
Heating	Yes	Warmer	Yes		
		Colder	No		

Design load			Seasonal efficiency				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Cooling	Pdesignc	7.1	kW	Cooling	SEER	7.10	-
Heating/Average	Pdesignh	7.1	kW	Heating/Average	SCOP/A	4.00	-
Heating/Warmer	Pdesignh	3.8	kW	Heating/Warmer	SCOP/W	6.40	-
Heating/Colder	Pdesignh	N/A	kW	Heating/Colder	SCOP/C	N/A	-

Cooling							
Declared capacity for cooling, at indoor temperature 27 (19) °C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27 (19) °C and outo	loor temper	ature Tj	
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 35°C	Pdc	7.10	kW	Tj = 35°C	EER d	2.93	-
Tj = 30°C	Pdc	5.20	kW	Tj = 30°C	EER d	4.95	-
Tj = 25°C	Pdc	3.30	kW	Tj = 25°C	EER d	8.05	-
Tj = 20°C	Pdc	1.60	kW	Tj = 20°C	EER d	15.24	-

Heating/Average							
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj			Declared coefficient of performance, at indoor temperature 20 °C and ou	,			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	6.20	kW	Tj = -7°C	COPd	2.23	-
Tj = 2°C	Pdh	3.80	kW	Tj = 2°C	COPd	3.80	-
Tj = 7°C	Pdh	2.40	kW	Tj = 7°C	COPd	6.00	-
Tj = 12°C	Pdh	1.10	kW	Tj = 12°C	COPd	7.33	-
Tj = bivalent temperature	Pdh	6.20	kW	Tj = bivalent temperature	COPd	2.23	-
Tj = operating limit	Pdh	6.20	kW	Tj = operating limit	COPd	2.17	-

Heating/Warmer								
Declared capacity for heating/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			Declared coefficient of performance/Warm at indoor temperature 20 °C and outdoor te		Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Tj = 2°C	Pdh	3.80	kW	Tj = 2°C	COPd	3.80	-	
Tj = 7°C	Pdh	2.40	kW	Tj = 7°C	COPd	6.00	-	
Tj = 12°C	Pdh	1.10	kW	Tj = 12°C	COPd	7.33	-	
Tj = bivalent temperature	Pdh	3.80	kW	Tj = bivalent temperature	COPd	3.80	-	
Tj = operating limit	Pdh	6.20	kW	Tj = operating limit	COPd	2.17	-	

Heating/Colder								
Declared capacity for heating/Colder season at indoor temperature 20 °C and outdoor	Declared coefficient of performance/Colde at indoor temperature 20 °C and outdoor temperature 20	,	e Tj					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Tj = -7°C	Pdh	N/A	kW	Tj = -7°C	COPd	N/A	-	
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-	
Tj = 7℃	Pdh	N/A	kW	Tj = 7°C	COP d	N/A	-	
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COP d	N/A	-	
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COP d	N/A	-	
Tj = operating limit	Pdh	N/A	kW	Tj = operating limit	COP d	N/A	-	
Tj=-15°C	Pdh	N/A	kW	Tj = -15°C	COP d	N/A	-	

Bivalent temperature			Operating limit temperature				
ltem	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heating/Average	Tbiv	-7	°C	Heating/Average	Tol	-15	°C
Heating/Warmer	Tbiv	2	°C	Heating/Warmer	Tol	-15	°C
Heating/Colder	Tbiv	N/A	°C	Heating/Colder	Tol	N/A	°C

Cycling interval capacity			Cycling interval efficiency				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
For cooling	Pcycc	N/A	kW	For cooling	EERcyc	N/A	-
For heating	Pcych	N/A	kW	For heating	COPcyc	N/A	-
Degradation coefficient cooling	Cdc	0.25	-	Degradation coefficient heating	Cdh	0.25	-

Electric power input in power modes other than 'active mode'				Annual electricity consumption			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Off mode (Cooling/Heating)	P _{OFF}	4.0/5.0	W	Cooling	Q _{CE}	350	kWh/a
Standby mode (Cooling/Heating)	P _{SB}	4.0/5.0	W	Heating/Average	Q _{HE}	2485	kWh/a
Thermostat-off mode (Cooling/Heating)	P _{TO}	1.0/7.0	W	Heating/Warmer	Q_{HE}	832	kWh/a
Crankcase heater mode (Cooling/Heating)	P _{CK}	0.0/0.0	W	Heating/Colder	Q _{HE}	N/A	kWh/a

Capacity control (Other items				
Item	Y/N	Item	Symbol	Value	Unit	
Fixed	No	Sound power level (Indoor/Outdoor)	L _{WA}	64.0/65.0	dB(A)	
Staged	No	Global warming potential	GWP	675	kgCO ₂ eq.	
Variable	Yes	Rated air flow (Indoor/Outdoor)	-	1040/2885	m³/h	

Contact details for obtaining more information	FUJITSU GENERAL LIMITED
Contact details for obtaining more information	3-3-17, Suenaga, Takatsu-ku, Kawasaki, 213-8502, Japan

V20121214